

Recommended Oil types DENO Compressors

The following lubrication types may be used for filling Piston compressors.
Compressor series; 2L, L2, L3, L4, 2K, 3K, 4K & DPA

<i>Brand</i>	<i>Type</i>
BP / Castrol	Aircol SN 100
Chevron / Texaco	Cetus DE100
Esso / Exxon	Synesstic 100
Shell	Corena S4P100

The following lubrication types may be used for filling Screw compressors.
Compressor series; DSA, DSR, DSD

<i>Brand</i>	<i>Type</i>	
	<i>Ambient temp <35°C</i>	<i>Ambient temp >35°C</i>
BP / Castrol	Aircol SR 46	Aircol SR 68
Chevron / Texaco	Cetus PAO 46	Cetus PAO 68
Esso / Exxon	Compressor Oil RS 46	Compressor Oil RS 68
Mobil	Rarus SHC 1025	Rarus SHC 1026
Shell	Corena S4R46	Corena S4R68
Total	Dacnis SH46	Dacnis SH68

IMPORTANT NOTE !!

When changing from original filling to any other lubricant, it is important to avoid that a mixture of lubricants with decreased properties is used.

- Drain oil from the crankcase completely.
- The first fill of chosen lubricant should be used for no longer than 1 hour after which the compressor should be drained and refilled with fresh lubricant again.